STAHLWILLE®

Torque wrench set

730R/40/32 Quick

Product no.	**96502053**
GTIN	**4018754082018**
Model	**730R/40/32 QUICK**

Label. Torque wrench set Model 730R/40/32 Quick 32 pcs.

Properties.

- for general maintenance work
- in steel case

Key features of torque wrench No. 730/40 Quick

- clicking type with dual stop signal
- no reset to '0' required, as the measuring element is only under load when a force is applied
- mount for interchangeable insert tools
- with QuickRelease safety lock
- Quick adjustment thanks to easy-to-operate locking lever in handle
- non-slip adjuster with thumb recess for quick torque adjustment
- double scale N·m/ft·lb or N·m/in·lb
- also available on request as a N·m only version without dual scale
- counter-clockwise tightening by turning the insert tools over
- clicking mechanism insensitive to continuous loads and counter-loads (up to the max. measurement range of the torque wrench)
- optimal calibration with perfectControl® calibration systems No. 7794 or calibration systems No. 7706, 7791
- easy adjustment without disassembly via 2 external adjustment screws
- with 2-component handle
- calibration certificate in accordance with DIN EN ISO 6789-2:2017
- **accuracy ± 4%**

Contains 32-pieces:

1 torque wrench Service MANOSKOP® **No. 730R/40 Quick**: measurement range: 80-400 N·m
1 ratchet insert tool, reversible 1/2" **No. 735/20**: 60 teeth
1 square drive insert tool 1/2" **No. 734/20**
7 open-ended insert tools **No. 731/40**: 13; 15; 17; 19; 22; 27; 30 mm
1 open-ended insert tool **No. 3731/40**: 24 mm
7 ring insert tools **No. 732/40**: 13; 15; 17; 19; 22; 24; 27 mm
10 sockets with bi-hex 1/2" **No. 50**: 13; 14; 15; 17; 19; 22; 24; 27; 30; 32 mm
1 T-handle 1/2" **No. 506**: L 300 mm
3 extensions 1/2" **No. 509**: L. 55; 130; 255 mm

Product highlights.

Rapid adjustment.
Easy and quick adjustment of the torque is carried out by an easy-to-operate clamping lever in the handle. The scale can be moved quickly and safely with an ergonomically shaped, non-slip adjustment element with thumb recess.

Adjustment does not require disassembly.
Quick adjustment from outside, no disassembly of the torque wrench required, with 2 adjustment points for the maximum & minimum values.

Technologies and features.

QuickRelease
The QuickRelease safety lock prevents unintentional loss of sockets and insert tools. These click securely into place, and are only released again at the push of a button for a quick tool change. In transducers: The QuickRelease safety lock helps you to quickly mount and change transducers. The transducers lock into the calibration system and only unlock again at the push of the buttons.



Low-wear bending beam system
Our torque wrench is equipped with a low-wear release system with a bending beam. Unlike conventional torque wrenches with coiled springs, the bending beam is not subjected to any load until the tool is in operation, which means that resetting to '0' is not necessary after use.

DIN EN ISO 6789-2
Our torque wrenches and torque screwdrivers are professionally calibrated in accordance with DIN EN ISO 6789-2 and delivered with a corresponding calibration certificate. We also calibrate angle-controlled torque wrenches in accordance with VDI 2648-2. This ensures the accuracy and traceability of our tools.

Technical attributes.

Anzeigeabweichung	± 4 %

Logistics data.

Product no.	96502053

Measuring range N·m	80-400 N·m	**GTIN**	4018754082018
Measuring range ft-lb	60-300 ft·lb	**Weight (g)**	9739 g
MA N·m	80 N·m	**Volume (packaged, dm3)**	10.192 dm3
Nominal value N·m	400 N·m	**Packing standard**	1
Scale division N·m	10 N·m	**WEEE/ElektroG**	nicht ear-pflichtig
Scale division ft-lb	10 ft·lb	**Customs tariff no.**	82060000
Length mm (L)	640 mm	**Country of origin AWR**	GERMANY
Width mm (b)	240 mm	**Region of origin**	Nordrhein-Westfalen
Height mm (h)	60 mm	**Depth mm (IFS)**	640
Type	Mercedes-Benz	**Width mm (IFS)**	245
Number of tools	32 pcs.	**Height mm (IFS)**	65
		Weight (gross, kg)	9,660
		Weight PAP (kg)	0,340
		Weight PVC (kg)	0,000
		Length (packaged, mm)	640
		Width (packaged, mm)	245
		Height (packaging, mm)	65

Parts list.

03010013
Socket

03010014
Socket

03010015
Socket

03010017
Socket

03010019
Socket

03010022
Socket

03010024
Socket

03010027
Socket

03010030
Socket

03010032
Socket

13010001
Extension

13010002
Extension

13010003
Extension

13070000
T-handle

50184040
MANOSKOP® torque wrench

58214013
Open-ended insert tool

58214015
Open-ended insert tool

58214017
Open-ended insert tool

58214019
Open-ended insert tool

58214022
Open-ended insert tool

58214027
Open-ended insert tool

58214030
Open-ended insert tool

58224013
Ring insert tool

58224015
Ring insert tool

58224017
Ring insert tool

58224019
Ring insert tool

58224022
Ring insert tool

58224024
Ring insert tool

58224027
Ring insert tool

58240020
Square drive insert tool

58250020
Fine-tooth ratchet insert tool

GTIN.

4 018754 082018

Images.

STAHLWILLE Eduard Wille GmbH
Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0
info@stahlwille.de · www.stahlwille.com
© STAHLWILLE Eduard Wille GmbH, Wuppertal